

65ALR Aluminium Cylinders Product offering

The 65ALR is a globally approved aluminium cylinder. The 875 litres nominal gas capacity means the cylinder is ideal when larger volumes of gas are required. The cylinder can be supplied with a range of CGA valves designed to meet your specific needs.

Characteristics						
	Contents	Typical Fill Pressure	Dimensions	Weight		
65ALR	875 Litres*	153 bar (2216 psig)	514 mm x 175 mm (20.25" x 6.9")	7.24 kg (16 lb)		

*Actual volume is dependant on vapour pressure of mixture

	Specifications						
	Approvals	Туре	Cylinder Valve	Recommended Equipment			
65ALI	R Global	Refillable Reactive Gases Only	CGA Type. Connection to cylinders varies with gas mixtures required.	Most commonly used regulators include 1000 Series, DFR 2003, or 718 with CGA connection.			





Contact Details

Americas

Global Headquarters Houston, TX, USA +1 713 624 8000

Customer Service and Manufacturing Facility Cambridge, MD, USA +1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Customer Service and **Manufacturing Facility** Stoke-on-Trent, United Kingdom +44 0808 164 8897

Middle East Sales Dubai, UAE +971 56 131 2346

South East Asia & Australia

Distribution Singapore +65 3163 9392

China

Customer Service and Distribution Shanghai +86 21 6090 3711

info@calgaz.com

www.calgaz.com