

## 8AL Aluminium Cylinders Product Offering

Calgaz has two types of 8AL cylinders designed to meet your needs. The 8ALE and 8ALU are both approved for global use and vary only slightly in terms of appearance and weight.

All cylinders have the universal C10 valve as standard and can be filled with both non-reactive and reactive gases.

Characteristic							
	Contents	Pressure	Dimensions	Weight			
8ALE	58 litres	35 bar (500 psi)	362 mm x 89 mm (14 1/4" x 3 1/2")	1.2 kg (2.65lb)			
8ALU	58 litres	35 bar (500 psi)	362 mm x 89 mm (14 1/4" x 3 1/2")	0.73 kg (1.6 lb)			



<sup>\*8</sup>ALU Picture

Specifications						
	Approvals	Туре	Cylinder Valve	Recommended Equipment		
8ALE	Global	Non-Refillable	C10	Most commonly used regulators include 700 Series, DFR 2000 Series, or 4200 Trigger regulators.		
8ALU	Global	Non-Refillable	C10			



# Contact Details

#### **Americas**

**Global Headquarters** Houston, TX, USA +1 713 624 8000

**Customer Service and Manufacturing Facility** Cambridge, MD, USA +1 800 638 1197

#### **Europe, Middle East &** Africa

Customer Service, Sales and Customer Service and **Manufacturing Facility** Stoke-on-Trent, United Kingdom +44 0808 164 8897

**Middle East Sales** Dubai, UAE +971 56 131 2346

### South East Asia & Australia

Distribution Singapore +65 3163 9392

#### China

**Customer Service** and Distribution Shanghai +86 21 6090 3711

info@calgaz.com

www.calgaz.com