



INDUSTRIAL FIXED

XNX™ Universal Transmitter

XNX™ Universal Transmitter

Overview



Feedback

Supports the widest range of sensors on a common platform and offers a modular choice of inputs and outputs (saving customers time and money).

Product Overview:

XNX's advantage comes from a simple-to-use, low-maintenance universal platform that works with other safety equipment on a digital bus system, including Honeywell Analytics' own Searchline Excel, Optima or other gas detectors, industry standard PLCs and third-party gas monitoring controllers.

XNX supports Electrochemical, Infrared and Catalytic Bead gas monitors and uses standard 4-20mA wiring and HART: options include Modbus, Fieldbus (pending) up to three relays and a local Hart Adapter for configuration and diagnostics using existing HART handheld devices.

With 200+ unique configurations, XNX satisfies Class 1/Class 2 intrinsically safe, explosion-proof requirements in upstream/downstream oil, chemical, wastewater and other industries.

The enclosure is available in stainless steel or aluminum, with a marine-grade coating. Five threaded ports, available in metric or NPT versions, and ruggedized mounting options provide ultimate installation flexibility. Instrumentation built on various sensing technologies can be attached locally to the transmitter or remotely with the appropriate accessories.

Features & Benefits:

- Flammable gas detection 0 to 100% LFL/LEL
- Flexible operation options
- Minimal training required

Quick Specs:

- Material: LM25 aluminum, painted (SS316 painted optional)
- Temperature: -40° to +65°C / -40° to +150°F (sensor dependent)
- Humidity: 20 to 90% RH (non-condensing)

Fire and Gas Consultancy Services

Even the best products deserve expert maintenance!

Elevate your gas detectors' potential with Honeywell's expert maintenance services! Maximize uptime, eliminate costs, and ensure on-time, on-budget project completion.

[Explore our fixed, portable, and high-tech support services now!](#)

Product Number

0060-1051	BEAD FERRITE MV XNX
0140-0008	BATTERY 3V LITHIUM HI-TEMP
0235-0238	XNX O-Ring W 0.139" OD 4.887"
1226-0254	Magnetic Wand/Screwdriver
1226-0257	M25 Stopping Plug w/ protective cap (stainless steel)
1226-0258	3/4" NPT Stopping Plug w/ protective cap (stainless steel)
1226-0299	IR SENSOR ELEMENT 5% VOL METHANE
1226-0300	IR SENSOR ELEMENT LEL FLAMABLE
1226-0301	IR SENSOR ELEMENT 5% VOL CARBON DIOXIDE
1226-0350	Sensor retainer, includes set screw (SS cover for EC sensor)

Alternative Products



[Sensepoint XCD RTD](#)

[Sensepoint XCD RTD](#)



[Sensepoint XCD](#)

[Sensepoint XCD](#)



[Series 3000 Mkll and Mklll Transmitters with Sensor](#)

[Series 3000 Mkll and Mklll Transmitters with Sensor](#)

Feedback

Honeywell
Safety and Productivity
Solutions
855 S Mint St
Charlotte, NC 28202
800-582-4263

XNX™ Universal Transmitter
© 2023 Honeywell International Inc.
All rights reserved.



This document was generated on 2023-12-19 4:47:16 PM (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.